

DRAWTEX WB-200

DEEP-DRAWING FLUID

PRODUCT DESCRIPTION

DRAWTEX WB-200 is a volatile forming and drawing fluid that contains special lubricants, anti-corrosion and EP additives.

APPLICATION / USAGE

DRAWTEX WB-200 is a product used in forming and deep drawing of steel, stainless steel and galvanized parts.

DRAWTEX WB-200 is used undiluted. It can be applied with rollers or a brush or sprayed with automatic lubricators.

ADVANTAGES / BENEFITS

- Offers high surface quality of the formed/ deep-drawn parts
- Ensures low consumption thanks to its low viscosity
- High performance even under difficult working conditions
- Good, temporary corrosion protection properties
- It evaporates within a short time after processing Completely, and therefore does not form any oily residue
- Since it is a volatile product and depending on the application, there is no need for cleaning operation. If washing is desired, it can be cleaned with water.

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

TECHNICAL PROPERTIES	TEST VALUES	TEST METHOD
Appearance	Light Yellow, Hazy	-
pH	8,91	ASTM D 1287
Kinematic Viscosity (40°C, cSt)	7,59	ASTM D 445

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

00.2022.01.01

